

THREE-PHASE SHUNT REACTOR 400V

PRODUCT CODE	Power (kVAr)	Current (A)	L (mH)	Connection	Dimensions (mm)			Mounting Size (mm)		Foot Installation	Weight (kg)
					A	B	C	D	E		
BRS3 400/0,5	0.5	0,72	1018,60	TERMINAL	150	150	72	100	55	M8	8
BRS3 400/1	1	1,44	509,03	TERMINAL	180	175	85	125	60	M8	11,5
BRS3 400/1,5	1.5	2,17	339,50	TERMINAL	180	175	115	125	90	M8	14,5
BRS3 400/2,5	2.5	3,61	203,72	TERMINAL	240	225	100	175	75	M8	17
BRS3 400/5	5	7,22	101,86	TERMINAL	295	255	170	200	135	M8	27
BRS3 400/7,5	7.5	10,83	67,90	TERMINAL	295	255	180	200	145	M8	39
BRS3 400/10	10	14,43	50,93	BUSBAR	355	310	170	250	135	M8	48
BRS3 400/12,5	12,5	18,04	40,74	BUSBAR	355	310	200	250	165	M8	57
BRS3 400/15	15	21,65	33,95	BUSBAR	410	360	180	250	145	M8	67
BRS3 400/20	20	28,86	25,46	BUSBAR	400	360	210	250	175	M8	80
BRS3 400/25	25	36,08	20,37	BUSBAR	400	360	225	250	200	M10	96,5
BRS3 400/50	50	72,20	10,20	BUSBAR	560	490	270	510	235	M10	200

